

Headwall



PRODUCT DATA SHEET



Nano-Hyperspec[®]
&
DJI MATRICE™ M600 Pro
Integrated & Flight-Ready!



THE FUTURE OF POSSIBLE

- Professional airborne performance
- Research-grade hyperspectral data
- High payload capacity; long-duration flight times
- Headwall-customized stabilizing gimbal
- Multiple flight-control redundancies
- 270 Spectral bands (VNIR 400-1000nm)
- Aberration-corrected imaging, wide FOV
- Airborne hyperspectral software
- Internal SSD data storage
- High spectral & spatial resolution



THE FUTURE OF POSSIBLE

PRODUCT DATA SHEET



DJI MATRICE™ M600 Pro*	
Diagonal wheelbase	1133mm
Dimensions	1668 mm × 1518 mm × 727 mm with propellers, frame arms and GPS mount unfolded (including landing gear). 437 mm × 402 mm × 553 mm with propellers, frame arms and GPS mount folded (excluding landing gear)
Weight (with six TB47S batteries)	9.5 kg
Max Takeoff Weight Recommended	15.5 kg
Hovering Accuracy (P-GPS)	Vertical: ±0.5 m, Horizontal: ±1.5 m
Max Angular Velocity	Pitch: 300°/s, Yaw: 150°/s
Max Pitch Angle	25 degrees
Max wind resistance	8 m/s
Max ascent speed	5 m/s
Max descent speed	3 m/s
Max service ceiling above sea level	2170R propellers: 2500 m 2195 propellers: 4500 m
Max speed	40 mph / 65 kph (no wind)
Flight time	Depends on payload and flying conditions
Retractable landing gear	Standard
Gimbal	Custom and stabilized for hyperspectral imaging
Standard battery	4500mAh
* Information above based on DJI-published specifications extracted from http://www.dji.com/matrice600-pro/info#specs on 13-March 2017.	

Nano-Hyperspec®	
Wavelength range	400-1000 nm
Spatial bands	640
Spectral bands	270
Dispersion/Pixel (nm/pixel)	2.2
FWHM Slit Image	6 nm
Integrated 2 nd order filter	Yes
f/#	2.5
Layout	Aberration-corrected concentric
Entrance Slit width	20 µm
Camera technology	CMOS
Bit depth	12-bit
Max Frame Rate (Hz)	300
Detector pixel pitch	7.4 µm
Max Power (W)	13
Storage capacity	480GB (~130 minutes at 100 fps)
Weight without lens, GPS (lb / kg)	1.2 / 0.5
Operating Temperature	0 °C to 50 °C

Nano-Hyperspec®

- 270 spectral bands
- 480GB on-board storage
- Fast Frame-Rate
- Small size, weight, power
- Aberration-corrected optics

March 2017

© 2017 Headwall Photonics, Inc. Information in this document is subject to change without notice. Headwall Photonics, Inc. reserves the right to change or improve its products and specifications and to make changes in content without obligation to notify any person or organization of such changes or improvements. The Hyperspec® name (and all its derivations) is a registered Trademark of Headwall Photonics, Inc. *US and/or EU Export Restrictions may apply to this Dual Use Product. MATRICE™ and the DJI logo are the property of DJI and used with their permission.



DC @M97 ; a V<
HY. Ž(- fl-&(' L* \$('%&' \$

Dc`ntYWD`Um`%!' +
: Ul. Ž(- fl-&(' L* -- '(

8`!+*' +K UXVfcb
9!AUJ. hsi4 dc`ntWXY

; 9FA5BM
k k k 'dc`ntWXY