



SHUTTER SERIES	ULTRAVIOLET .3-.4µm (microns)		VISIBLE .4-.75µm (microns)		INFRARED .75– 10.6µm (microns)	
	(Z) AISiO	(ZM) AlMgF <sub>2</sub>	(Z) AISiO	(ZM) AlMgF <sub>2</sub>	(Z) AISiO	(ZM) AlMgF <sub>2</sub>
NS45B	N/A	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>
NS65B	N/A	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>
TS2B	N/A	2.5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>
TS6B	N/A	2.5 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>	2.5 W/mm <sup>2</sup>
VS14	N/A	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>
VS25	N/A	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>
VS35	N/A	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>	10 W/mm <sup>2</sup>	5 W/mm <sup>2</sup>
XRS14	N/A	N/A	N/A	N/A	N/A	N/A
XRS25	N/A	N/A	N/A	N/A	N/A	N/A
XRS6	N/A	N/A	N/A	N/A	N/A	N/A

The question regarding enhancement of shutter speed with the application of user supplied lubricants has been repeatedly asked. It is our experience that lubricating the shutter blades will actually slow the shutter down and eventually render the shutter inoperable. UNDER NO CIRCUMSTANCES SHOULD ANY TYPE OF LUBRICANT BE APPLIED TO THE SHUTTER BLADE AREA.

